

Olex2 Manual (Commands)

Draft: December, 2010

1. Introduction	2
2. Understanding the Syntax	2
3. Tables of Olex2 Commands	3
Changing the Model View	3
Keyboard Shortcuts	4
Fixed/Refined Parameters	5
Atom Connectivity Table Manipulation	6
Symmetry Operations	8
Disorder Modelling: Constraints and Restraints	9
Selection Syntax	12
HKL file Operations	12
Customising the Olex2 GUI	13
Output: Tables, Reports and Images	15
Structure Analysis	16
4. How to...?	18
Overlay molecules	19
Copy naming scheme from one fragment to another	20
Get esd's on geometric measurements	21
Get a stereo view	21
Pack or grow molecule(s)	22
Change P1 space group to P-1	23
Change space group settings	24
To control console and graphics visibility	24
Select atoms that became 'too small'	25
Use ShelX programs in Olex2	25
Change default programs	25
Working with the Maps display	26
Fix tooltips problems	26
5. Appendix	0
About Versions and Tags	27
Installing Olex2	27
Windows:	27
External Programs	28
SHELX	28
Platon	29
SuperFlip	29



This document describes some of the commands that are available in Olex2. Many of these commands are also available directly from the Olex2 Graphical User Interface. Most items on the GUI have a small 'info' symbol next to them, where you can find out more about any of these items.

1. Introduction

There is no special console window in Olex2 – the commands described in this document can be typed where ever you are in Olex2 and the text you type (as well as the program response) will appear in the bottom left hand corner of the main window. The text will then scroll up behind the displayed molecule. The number of lines of text that are visible can be set with the command **lines *n***. You can also toggle between showing the **molecule only**, showing the **text only** and showing both at the same time (default) using **CTR+T**. You can always examine the text output in your default text editor by typing **text**.

Many commands in Olex2 are modelled on the syntax that may be familiar from SHELX: four letter commands, where the letters often provide a hint about the function of the command. Many commands that are available in ShelXP, for example, can be used in Olex2. Also, all commands of the ShelXL and ShelXS syntax are interpreted by Olex2 and used to construct the internal Olex2 structure model. This model is then used directly to carry out a smtbx-refine refinement, whereas a shelx.ins file is generated on the fly if ShelXL/XH is chosen for the refinement.

All commands in Olex2 will **auto-complete** when pressing the TAB key. If the completion is not possible, because there is more than one command starting with the letters that have been typed, a list of these commands will be printed. It is good practice to use the auto-complete feature!

2. Understanding the Syntax

Selection: If one or more atoms are selected on the screen, then any command that acts on a selection will apply to the **selected atoms only**. If there is no selection, it will apply to **all** atoms. Instead of making a selection on the screen, a list of atom names can also be supplied. *If a command has been successful, the selection will disappear. (Although there are a couple of exceptions to this rule)*

Mode: If Olex2 is in a **Mode**, the chosen action will be applied to all subsequently clicked atoms. The mouse pointer will change from the default arrow symbol to signify that Olex2 is in a mode. To get out of a mode, simply press the **ESC** key.

Syntax used in this document:

{a, b, c}: choice of a, b or c. For example: fix {occu, xyz, Uiso} [atoms] means 'fix occu [atoms]', 'fix xyz [atoms]', 'fix Uiso [atoms]'.

[val=2]: optional parameter. This parameter is not required for the command to work, and if it is not supplied, the default value will be used.

-k: This is an option switch.

i: Italic characters are used for variables.

[atoms] means an optional list of atoms. Any atoms that are selected will automatically be present in this list. If there are no selected atoms, **all** atoms will be in this list. Alternatively, the atom names of the atoms that should appear in this list can be typed by hand.

atoms means a compulsory list of atoms. Any atoms that are selected will automatically be present in this list. Alternatively, the atom names of the atoms that should appear in this list can be typed by hand.

Capital Letters are used for commands that will directly affect the structure model in the refinement. These commands will become part of the structure model and will appear in the ShelX input file. Please note that these commands can be typed either in upper or lower case.

Example Commands are represented in this format: **refine 4 20** and can be typed exactly as they are given. In this example, the structure will be refined with 4 refinement cycles and 20 electron density peaks will be returned from the electron density map integration.

3. Tables of Olex2 Commands

3. 1 Changing the Model View		
matr	[1,2,3 or abc] or [abc a1b1c1] or [x11 x12 x13 y11 y12 y13 z11 z12 z13]	Orients the model along a (1 or 100), b (2 or 010), c (3 or 001) or any other crystallographic direction, like 123, which sets current normal along (1*a+2*b+3*c) vector. Two crystallographic directions (from and to) may be specified align current view normal along the (to-from) vector. Also a full Cartesian matrix can be specified. If the directions are signed or consist of multiple digits all components should be of the same length like in 120101 or -1+1+1 (same as -10101). If no arguments given, prints current Cartesian orientation matrix.

		Examples: <ul style="list-style-type: none"> • matr 1 or matr a or matr 100 - sets current normal along the crystallographic a direction • matr 100 011 sets current normal along (011-100) direction (the normal direction changes if from and to are swapped)
rota	[axis angle] or [x y z angle increment]	<p>Changes current view by rotating around given axis (x, y or z) when two arguments are provided and makes a continuous rotation around give axis when 5 arguments are provided. Note that X axis is aligned horizontally, Y - vertically and Z is out of the screen plane.</p> <p>Examples:</p> <ul style="list-style-type: none"> • rota x 90 rotates the structure 90 degrees around X axis • rota 0 0 1 90 1 rotates model in the screen plane (around Z) 90 degrees with 1 degree increment.
direction		The command prints current normal in crystallographic coordinates and tries to match it to a crystallographic direction.
mpln	[atoms] [-n] [-r]	<p>Finds the best plane through the current selection or given atoms, or out of all visible atoms if none are given.</p> <ul style="list-style-type: none"> • -n: sets the view along the normal of the plane • -r: creates a regular plane

The model can be **rotated** using by moving the mouse pointer while holding the left mouse button down (also Shift+arrow keys); **rotated around Z** by pressing the **CTRL** key down while rotating; **zoomed** using the right mouse button (also Shift+Home/End or Alt key+left mouse button); **shifted in the viewing plane** by pressing Ctrl+Shift and holding the right mouse button down. The default mouse behaviour can be overridden in some modes (look at mode split) also some objects, like cell basis or text boxes can override some mouse operations (like zooming on the cell basis) or extend it (moving the basis while holding Shift key down).

3. 2 Keyboard Shortcuts

CTRL+Q	ShowQ	Toggles between three states: <ul style="list-style-type: none"> • show electron density peaks • show electron density peaks with bonds • hides electron density peaks
CTRL+H	ShowH	

		<p>Toggles between three states:</p> <ul style="list-style-type: none"> • show hydrogen atoms • show hydrogens with internal h-bonds • hides hydrogen atoms
CTRL+T	ShowStr	<p>Toggles between three states:</p> <ul style="list-style-type: none"> • show structure only • show show structure and text • show text only
CTRL+I	sel -i	Inverts the current selection.
CTRL+A	sel -a	Selects all atoms currently visible, however if labels are active (i.e. one or more label is selected) then this selects all labels.
CTRL+U	sel -u	Deselects all of current selection.
CTRL+G	mode grow	Enters mode grow. See also symmetry operations .
CTRL+O	reap	Brings up the Open File dialogue.
F2	swapbg	Swaps the background between white and coloured.
F3	labels	Toggles labels on/off.
F4	grad -i	Toggles gradient background on/off.
F5		Go to the work menu.
F6		Go to the view menu.
F7		Go to the tools menu.
F8		Go to the info menu.
F11	Fullscreen(true/false)	Toggles full screen mode on/off.
Shift+F11	HtmlPanelVisible	Toggles html panel on/off.
ESC		Exits current mode (some modes, like mode <i>match</i> , can override this), clears current selection and text in the command line
Break		Interrupts the solution/refinement after the current cycle.
Del (Ctrl+Backspace on Mac)	kill	Deletes selected object

3. 3 Fixed/Refined Parameters

fix	{occu, xyz, Uiso} [atoms]	<p>Fixes the specified refinement parameter, ie these parameters will not be refined in subsequent refinement cycles.</p> <ul style="list-style-type: none"> • occu: will fix the occupancy • xyz: will fix the xyz coordinates • Uiso: will fix the whole ADP <p>Examples:</p> <ul style="list-style-type: none"> • fix occu 0.5: will set and fix the occupancy of the current selection to 0.5 • fix xyz: will fix the x, y and z co-ordinates of the currently selected atoms, ie not refine them.
free	{occu, xyz, Uiso} [atoms]	The opposite of fix - makes the specified parameters for the given atoms refineable. Freeing the occupancy is also available from the context menu.
mode	fixu	Fixes Uiso or ADP for subsequently clicked atoms.
mode	fixxyz	Fixes coordinates for subsequently clicked atoms.
mode	occu occupancy_to_set	Sets atoms occupancy to the provided value for subsequently clicked atoms.
<p>labels -f show currently fixed atomic parameters, labels -f -r show labels for fixed atoms and also the number at which the occupancy of riding atoms is fixed</p>		

3. 4 Atom Connectivity Table Manipulation

conn	n [r] atoms	<p>Sets the maximum number of bonds for the specified atoms to n and changes the default bond radius for the given atom type to r.</p> <p>Examples:</p> <ul style="list-style-type: none"> • conn 5 \$C sets the maximum number of bonds all C atoms can have to 5, • conn 1.3 \$C changes the bonding radius for C atoms to 1.3 (the floating point is used to distinguish between n and r in this case!), • conn 5 1.3 \$C combines the two commands above
-------------	------------------------------------	---

compaq	[-a] [-c] [-q]	<p>Moves all atoms or fragments of the asymmetric unit as close to each other as possible. If no options are provided, all fragments are assembled around the largest one.</p> <ul style="list-style-type: none"> • -a: assembles broken fragments • -c: similar to the default behaviour, but considers atom-to-atom distances and will move all atoms to the closest possible position to the largest fragment in the structure. • -q: moves the electron density peaks close to the atoms.
addbond	A1 A2 or atoms	<p>Adds a bond to the connectivity list for the specified atoms. This operation will also be successful if symmetry equivalent atoms are specified.</p>
delbond	A1 A2 or Selected bond(s)	<p>Removes selected bonds from the connectivity list.</p>
sort	[m] [l] [p] [h] atoms [s] [h] [m] moiety	<p>The sorting of atoms in the atom list is very powerful, but also quite complex .</p> <ul style="list-style-type: none"> • -m: atomic weight • -l: label, considering numbers • -p: part, 0 is first followed by all positive parts in ascending order and then negative ones • -h: to treat hydrogen atoms independent of the pivot atom. <p>Sorting of moieties</p> <ul style="list-style-type: none"> • -s: by size • -h: by heaviest atom • -m: by molecular weight <p>Usage:</p> <ul style="list-style-type: none"> • sort [+atom_sort_type] TBA <p>sort [Atoms] [moiety [+moiety_sort_type] [moiety_atoms]] If just 'moiety' is provided - the atoms will be split into the moieties without sorting.</p> <p>Examples:</p> <ul style="list-style-type: none"> • sort +m1 F2 F1 moiety +s will sort atoms by atomic mass and label, put F1 after F2 and form moieties sorted by size. Note that when sorting atoms, any subsequent sort type operates inside the groups created by the preceeding sort types.
Olex2 will display the altered connectivity table in the case if structure is grown or packed		

3. 5 Symmetry Operations

lstsymm		Prints symmetry operations and their codes for current structure.
envi	<p><i>[r=2.7 Å] A1 or one selected atom [-h] [-q]</i></p> <p>Note: if more than one atom is selected the first one is used</p>	<p>Prints a list of those atoms within a sphere of radius r around the specified atom.</p> <ul style="list-style-type: none"> • -h: adds hydrogen atoms to the list • -q: option adds Q-peaks to the list
mode	grow [-s] [-v] [-b]	<p>Displays the directions in which the molecule can be grown</p> <ul style="list-style-type: none"> • -s: also shows the short interaction directions • -v: [2.0 Å] shows directions to the molecules within v value of the Van der Waals radii of the selected atoms which can be generated by clicking on the direction representations, only unique symmetry operations (producing shortest contacts are displayed) • -r: shows directions to all symmetry equivalent atoms of the selected one(s) within 15 Å • shortcut CTRL+G is used to enter the 'mode grow'
mode	pack	Displays the position of symmetry equivalent asymmetric units as tetrahedra. These asymmetric units can be generated by clicking on the corresponding tetrahedron.
sgen	<p>atoms</p> <p>The Symmetry operation is represented as 1_555, 1555 or -1+X,Y,Z and atoms as a selection or a names list</p>	<p>Generates symmetry equivalents of the provided (or all atoms, if there is no selection) using the provided symmetry operation.</p> <p>Note: For symmetry operations starting with '-' and letter, a leading zero must be added, for example, 0-x,-y,-z, otherwise Olex2 confuses this with an option.</p>
pack	a_from a_to b_from b_to c_from c_to [atoms]	<p>Packs all or specified atoms within given dimensions</p> <ul style="list-style-type: none"> • -c: prevents clearing existing model <p>Example: pack \$O will pack all O atoms with the default of -1.5 to 1.5 cells range.</p>

pack	from to	Equivalent to ' pack from to from to from to ', like ' pack o 1 ' is expanded to ' pack o 1 o 1 o 1 '
pack	cell	Shows content of the unit cell. In conjunction with ' grow -w ' allows the creation of views where all asymmetric units contributing to the unit cell are shown.
pack	r	Packs fragments within radius r of the selected atom(s) or the centre of gravity of the asymmetric unit.
grow	[atoms] [-w]	<p>Grows all possible/given atoms; for polymeric structures or structures that require to be grown several times Olex2 will continue grow until the operation results in a symmetry element that has been used previously.</p> <ul style="list-style-type: none"> • -w: permits the application of symmetry previously used operations to other fragments of the asymmetric unit <p>Example: If the main molecule is grown, but only one solvent molecule is shown, using 'grow -w' will produce other solvent molecules using symmetry operators used to grow the main molecule</p>

If some atoms are deleted after growing operations, Olex2 will use existing unique atoms as the asymmetric unit atoms; this can be helpful to avoid a sequence of sgen/kill commands.

labels -l -i: Adds labels only to the 'original' - i.e. not created by symmetry - molecule.

In a packed structure: **Right-click on a bond > Graphics > Select the Groups(s):** Will select all bonds (or atoms) of that type in the grown structure.

3. 6 Disorder Modelling: Constraints and Restraints

EXYZ	atom types (to add for the selected atom) [-EADP] [-lo]	<p>Makes the selected site shared by atoms of several atom types.</p> <ul style="list-style-type: none"> • -EADP: adds the equivalent ADPs command for all atoms sharing one site. • -lo: links the occupancy of the atoms sharing the site through a free variable.
EADP	atoms	Makes the ADP of the specified atoms equivalent.

SADI	atoms or bonds [esd=0.02]	<p>For selected bonds or atom pairs SADI makes the distances specified by selecting bonds or atom pairs similar within the esd.</p> <p>If only one atom is selected it is considered to belong to a regular molecule (like PF₆) and adds similarity restraints for P-F and F-F distances.</p> <p>For three selected atoms (A1,A2,A3) it creates similarity restraint for A1-A2 and A2-A3 distances.</p>
DFIX	d atom pairs or pairwise selection in order [esd=0.02]	<p>For selected bonds or atom pairs DFIX will generate length fixing restraint with the given esd.</p> <p>If only one atom is selected, all outgoing bonds of that atom will be fixed to the given length with provided esd. For three selected atoms (A1,A2,A3) the A1-A2 and A2-A3 restraints will be generated.</p>
DANG	d atom pairs or pairwise selection in order [esd=0.04]	For selected bonds or atom pairs, distance restraints similar to dfix will be generated.
tria	d1 d2 angle [esd=0.02]	<p>For given set of bond pairs sharing an atom or atom triplets generates two dfix commands and one dang command.</p> <p>Example: tria 1 1 180 C1 C2 C3 will generate 'DFIX 1 0.02 C1 C2 C2 C3' and 'DANG 2 0.04 C1 C3' it will calculate the distance for dang from d1 d2 and the angle.</p>
FLAT	[atoms][esd=0.1]	Restrains given fragment to be flat (can be used on the grown structure) within given esd.
CHIV	[atoms][val=0] [esd=0.1]	Restrains the chiral volume of the provided group to be val within given esd
SIMU	[d=1.7] [esd12=0.04] [esd13=0.08]	Restrains the ADPs of all 1,2 and 1,3 pairs within the given atoms to be similar with the given esd.
DELU	[esd12=0.01] [esd13=0.01]	'rigid bond' restraint
ISOR	[esd=0.1] [esd_terminal=0.2]	Restrains the ADP of the given atom(s) to be approximately isotropic

SAME	N	Splits the selected atoms into the N groups and applies the SAME restraint to them. Olex2 will manage the order of atoms within the ins file, however mixing rigid group constraints and the 'same' instructions might lead to an erroneous instruction file.
showp	[any]; space separated part number(s)	Shows only the parts requested: showp 0 1 will show parts 0 and 1, showp 0 just part 0. showp by itself will display all parts.
split	[-r={eadp, isor, simu}]	Splits selected atom(s) along the longest ADP axis into two groups and links their occupancy through a free variable. <ul style="list-style-type: none"> • -r: adds specific restraints/constraints (EADP, ISOR or SIMU) for the generated atoms
AFIX	shelx afix number{mn} [-n]	If no are atoms provided and afix corresponds to a fitted group where n is 6 or 9 (such as 106 or 79), all the rings which satisfy the given afix will be automatically made rigid (this is useful in the case of many PPh3 fragments); alternatively a single ring atom can be selected to make that ring rigid. In other cases, depending on afix either 5,6 or 10 atoms will be expected. Special cases of afix 0, 1 and 2 can be used to remove afix, fix all parameters or leave just the coordinates refinable, all other afix instructions will consider the first atom as a pivot atom and the rest - dependent atom. <ul style="list-style-type: none"> • -n: consider N-atoms as parts of rings
part	[part =new_part] [atoms] [-p=1]	Changes part number for given/selected atom; <ul style="list-style-type: none"> • -lo: links occupancies of the atoms through a +/-variable or linear equation (SUMP) depending on the -p[=1] • -p: specifies how many parts to create. If -p=1, -lo is ignored and the given or new part is assigned to the provided atoms.
fvar	[value] [atoms]	This command links two or more atoms through a free variable. <ul style="list-style-type: none"> • If no atoms are given the current free variables are printed. • If no value is given but two atom names are give, the occupancies of those atoms are linked through a new free variable. • If a value of 0 is given, the occupancy of the specified atoms will be refined freely • if the value is not 0, the occupancy value of the specified atoms is set to the given value.

sump	[<i>val</i> =1] [<i>esd</i> =0.01]	<p>Creates a new linear equation. If any of the selected atoms has refinable or fixed occupancy, a new variable is added with value 1/(number of given atoms), otherwise already used variable is used with weight of 1.0.</p> <p>Example: If 3 atoms (A1, A2, A3) are selected this command will generate three free variables and insert the r2 1.0 var 3 instruction (equivalent to $1.0 = 1.0 \cdot \text{occu}(\text{A1}) + 1.0 \cdot \text{occu}(\text{A2}) + 1.0 \cdot \text{occu}(\text{A3})$).</p>
mode	split [- <i>r</i> ={eadp, isor, simu}]	<p>Splits subsequently clicked atoms into parts, or in combination with the Shift key can be used to drag an atom to change its position. While in the mode the newly generated atoms can be selected and moved as a group with Shift down or rotated when dragging the selection. The original and generated atoms will be placed into different parts.</p> <ul style="list-style-type: none"> • -r: can be used to generate extra restraints or constraints for original and generated atoms (see also the '<i>split</i>' command); values EADP, ISOR or SIMU are allowed

3.7 Selection Syntax

sel	sel atoms where xatom.bai.mw > 20	Will select all atoms where the atomic mass is larger than 20
sel	Symmetry operation (represented by 1_555 or 1555)	Will select all currently shown symmetry generated atoms which were generated by the symmetry operation given.
sel	sel rings NC5	Will select all NC5 rings in the structure
sel	sel part 1	Will select part 1 of the structure

3.8 HKL file Operations

hklstat		Prints detailed information about reflections used in the refinement.
----------------	--	---

omit	h k l	Inserts 'OMIT h k l' instruction in the ins file
omit	val	Inserts 'OMIT h k l' for all reflections with $ Fo^2 - Fc^2 > val$.
omit	s 2theta	Inserts 'OMIT s 2theta' instruction in the ins file
edithkl	[h k l]	<p>Brings up a dialogue, where 'bad' reflections from the Shelx lst file and all its constituent symmetry equivalents can be inspected and flagged to be excluded from the refinement.</p> <p>In contrast to the OMIT h k l instruction, which excludes the reflection and <i>all its equivalents</i>, this dialogue allows to exclude those equivalents that are actually outliers.</p> <p>If a particular reflection is specified, this particular reflection and all its constituent equivalents can be viewed.</p>
excludehkl	-h=h1;h2;.. -k=k1;k2.. -l=l1;l2.. [-c]	<p>This function provides a mechanism to reversibly exclude some reflections from refinement (these reflections will be moved to the end of the hkl file so they appear after the o o o reflection).</p> <ul style="list-style-type: none"> • -c: option controls how the given indices are treated, if not -c option is provided, then any reflection having any of the given h, k or l indices will be excluded, otherwise only reflections with indices within provided h, k and l will be excluded.
appendhkl	-h=h1;h2;.. -k=k1;k2.. -l=l1;l2..	Acts in the opposite way to excludehkl

For more advanced HKL processing, a Python script may be used. A sample hklf5.py script is provided in {Olex2 folder}/etc/scripts. The script can be copied and modified to accommodate any particular twinning law and run inside Olex2. The script allows creating an HKLF 5 file where reflections which belong to different twin components are assigned different batch numbers. To run a python script in Olex2 use the following command to load the script:

```
>>@py -l
```

This command shows a 'File Open' dialog, a python script can be selected. After loading the script can be modified and executed by pressing OK.

3. 9 Customising the Olex2 GUI

setfont	{Console, Picture_labels}	Brings up the dialog to choose font for the Console or Labels which end up on the picture. Built in function choosefont([olex2]) to choose system or specially prepared/portable font can be used to specify the font.
EditMaterial	{helpcmd, helptxt, execout, error, exception, any object name available with <i>lstgo</i> }	<p>Brings up a dialog to change properties of the specified text section or graphical object.</p> <ul style="list-style-type: none"> • helpcmd - material for the command name in the help window • helptxt - material for the body of the help item • execout - material for the output text printed in the console of external programs • error - material for reporting errors in the console • exception - material for reporting exception in the console <p>This command can be used to edit properties of any objects printed by '<i>lstgo</i>' macro. An example of that could be editing material of the console text:</p> <p>EditMaterial Console</p> <p>Note that the object name is case sensitive.</p>
save	{scene, style, view, model} [file_name]	<p>If the file name is not provided, the 'Save as...' dialog will be shown which allows to save current settings to file. The scene save current font names/sizes as well as the materials for the specific console output, like external programs output, error and exception reporting.</p> <p>The style saves information about the appearance of objects in the scene.</p> <p>The view saves current zoom and the scene orientation.</p> <p>The model saves current view including the crystallographic mode and style.</p>
load	{scene, style, view model} [file_name]	Load one of the previously saved items. If no file name is provided, the 'Open file...' dialog will appear, otherwise if just a file name is provided (the extension will be guessed by Olex2), for styles and scene the last used folders will be used by default, whereas the current folder will be used for the views and models.
grad	[C1 C2 C3 C4] [-p]	<p>Choose the colour of the four corners of the graduated background.</p> <ul style="list-style-type: none"> • -p: a file name for the picture to be placed at the background
brad	r [hbonds] operates on all or selected bonds	Adjust the bond radii in the display. If the 'hbonds' is provided the second argument, the given radius is applied to all hydrogen bonds.
ads	{elp, sph, ort, std}	<p>A function for drawing styles development. Changes atom draw style for all/selected atoms.</p> <ul style="list-style-type: none"> • elp - represents atoms as ellipsoids (if ADP is available)

		<ul style="list-style-type: none"> • sph - represents atoms as spheres • ort - same as elp, but spheres have one of the quadrants cut out • std - a standalone atom (i.e. grown as a cross in wire-frame mode)
arad	{sfil, pers, isot, isoth, bond, vdw}	<p>A function for drawing styles development; applies different radii to all/selected atoms.</p> <ul style="list-style-type: none"> • sfil - sphere packing radii (as in ShelXTL XP) • pers - a fixed radii for model viewing • isot - each atom has it's own radius depending on the value of the Uiso or ADP • isoth - same as isot, but the H atoms are also displayed with their real Uiso's • bond - all atoms get same radii as default bond radius • vdw - the default/loaded Van der Waals radii used in most of the calculations
azoom	% [atoms]	Changes the radii of all/given atoms, the change is given in percents.

3. 10 Output: Tables, Reports and Images

pictPS	filename.ps	<p>Generates a post-script file of what is visible in the molecule display.</p> <ul style="list-style-type: none"> • -atom_outline_color - the colour of the atom outline, used for extra 3D effect for the intersecting objects [0xFFFFFF] • -atom_outline_oversize - the size of the outline [5]% • -bond_outline_color - same as for the atom, can be changed to black to highlight bond boundaries • -bond_outline_oversize - the size of the outline [10]% • -color_fill: Fills the ellipses with colour. • -color_bond: Bonds will be in colour. • -color_line: Lines representing the ellipses will be in colour. • -div_pie: number [4] of stripes in the octant • -lw_ellipse: line width [0.5] of the ellipse • -lw_font: line width [1] for the vector font • -lw_octant: line width [0.5] of the octant arcs • -lw_pie: line width [0.5] of the octant stripes • -p: perspective • -scale_hb: scale for H-bonds [0.5] <p>The bond width is taken from the display. This can be changed with brad</p>
---------------	-------------	---

pict	filename.ext [<i>n</i> =2] [-pq]	Generates a bitmap image of what is visible on the molecule display. <i>n</i> Refers to the size of the output image. If <i>n</i> is smaller than 10, it refers to a multiple of the current display size, if it is larger than 100, it refers to the width of the image in pixels. <ul style="list-style-type: none"> ext {png, jpg, bmp}. png is best. -pq: print quality
picta	filename.ext [<i>n</i> =1] [-pq]	A portable version of pict with limited resolution (see explanation for <i>n</i> above), which is OS and graphics card dependent. This may not be stable on some graphics cards <ul style="list-style-type: none"> -pq: print quality -n: as for 'pict'
picts	filename.ext [<i>n</i> =1] [-a=6] [-s=10] [-h= <i>n</i> *(screen height)]	Creates a 'stereo' picture with two views taken with the +/- <i>a</i> option value rotation around y axis and placed onto one picture separated by <i>s</i> % of a single projection width. <ul style="list-style-type: none"> -a: half of the view angle -s: separator width in % -h: the height of the output, by default equals to current screen height multiplied by the given resolution
label	label [<i>atoms</i>]	Adds labels to all/given/selected atoms. These labels can be moved by pressing the SHIFT key while holding down the left mouse button and edited by double clicking on them. <ul style="list-style-type: none"> -type: {subscript, brackets, default}, the type only affects the PostScript labels and not applicable to the raster pictures

3. 11 Structure Analysis

There are various tools available for the analysis of structures.

htab	[minimal angle=150°] [maximum bond length 2.9 Å] [-t] [-g]	Searches and adds found hydrogen bonds (like HTAB and RTAB in Shelx) into the list for the refinement program to add to the CIF. Equivalent symmetry positions are automatically inserted and merged with the existing ones. The command can be executed several times with different parameter values, only one unique instructions will be added. <ul style="list-style-type: none"> -t: adds extra elements (comma separated like in -t=Br,I) to the donor list. Defaults are [N,O,F,Cl,S] -g: if any of the found bonds are generated by symmetry transformations, the structure is grown using those symmetry transformation
-------------	---	--

pipi	[centroid-to-centroid distance 4 Å] [centroid-to-centroid shift 3 Å] [-g] [-r=C6,NC5]	<p>The command analyses the p-p interactions (only stacking interactions for now) for flat regular C6 or NC5 rings and prints information for the ones where the intercentroid distance is smaller than [4] Å and the intercentroid shift is smaller than [3] Å.</p> <ul style="list-style-type: none"> • -g: if any of the rings is fully or partially constructed of symmetry generated atoms it grow the structure using those symmetry operators • -r: ring content, the defaults are C6 and NC5 rings, the rings are tested for being flat and regular
calcvoid	[radii file name] [all atoms/selected atoms] [-d=0] [-p] [-r=0.2Å]	<p>Calculates and displays the structure map. Also calculates the largest channels along crystallographic directions and the packing index.</p> <ul style="list-style-type: none"> • -d: extra distance from the surface (added to the atomic radii) • -p: precise calculation, each map voxel is tested, the default quick algorithm, uses the atom masks to find volume occupied by the molecule. The precise calculation is vectorised • -r: resolution, a resolution of at least 0.1Å and -p options is required to get values for publishing <p>Note: The radii used in the calculation are currently coming from the CSD website: http://www.ccdc.cam.ac.uk/products/csd/radii However there are several ways how the radii can be changed, one of the ways is to provide a file name with radii ([element radius] a line format), the other one is to load the radii from the same kind of the file using 'load radii vdw' command.</p>
molinfo	[radii file name] [atoms] [-g=5] [-s=0]	<p>Calculates molecular volume and the surface area for all/selected atoms.</p> <ul style="list-style-type: none"> • -g: generation of the triangulation process • -s: source of the triangles for the sphere triangulation, [o]ctahedron or [t]etrahedron are available <p>Generation 5 for octahedron approximate sphere by 8192 triangles, for tetrahedron by 4096 triangles, each generation up increases the number of triangles by factor of 4, generation down - decreases it by the same factor.</p>
calcfourier	{-calc,- diff, -obs, -tome} [-r=0.25Å] [-i] [-scale=simple] [-fcf]	<p>Calculates Fourier for current model</p> <ul style="list-style-type: none"> • -r: the resulting map resolution in angstroms • -i: integrate the calculated map • -scale: when Olex2 calculates structure factors, it uses the linear scale as a $\sum(F_o^2)/\sum(F_c^2)$ by default, however a linear regression scale can be also used (use -scale=regression)

		<ul style="list-style-type: none"> • -fcf: Olex2 will use an FCF with LIST 3 structure factors as a source of the structure factors. If this option is not specified, Olex2 will calculate the structure factors using the the reflection used in the refinement (use the 'hklstat' command to see more information on reflections).
calcpatt		Calculates and displays Patterson map
match	[atoms] [-a] [-c=geom] [-i] [-n] [-u] [-esd]	<p>This procedure find relation between the connectivity graphs of molecular fragments of loaded structure and aligns the fragments. If no arguments are given, the procedure analyses all fragments and in the case fragments with matching connectivity found, aligns¹ them and prints corresponding root mean square distance (RMSD) in angstroms. If two atoms are provided (explicitly by name or through the selection) the graph relation information - orientation matrix and the matching atoms is printed, use -a option to align the fragments.</p> <ul style="list-style-type: none"> • -a: align the fragments (used when a pair of atoms is provided) • -c: specifies in which way the centre of molecule is calculated - (geom)etric or (mass). Programs like XP and Mercury use the geometric molecular centre (i.e. calculated with unit weights for the atoms), this is also the default for Olex2, however if heavier atoms are to be given a higher weight, the atomic mass can be used as the weight • -i: try to invert one of the fragments • -n: transfer labels from one fragment to another (two atoms should be provided for <i>from</i> and <i>to</i> fragments. If the value a symbol [or set of] this is appended to the label, '\$xx' replaces the symbols after the atom type symbol with xx, leaving the ending, '-xx' - changes the ending of the label with xx. Note that if the molecules match with -i options, this should also be provided for the label transfer • -u: restores the coordinates of the matched fragments, this is useful if grown structure is matched • -esd: if the variance-covariance matrix can be located (after the refinement with the negative MORE option in the xl), the esd on the RMSD can be calculated using this option <p>See the 'How to...?' section for more information.</p>
Notes etc about Structure Analysis		

4. How to...?

4. 1 Overlay molecules

Olex2 provides several tools to match/align/overlay fragments or molecules. If the fragments have the same connectivity, the user can just type 'match' for automatic matching of the molecules. Olex2 will search for molecular graphs of the same connectivity* and align them, printing corresponding RMSD in angstroms. If the structure has more than two fragments, one atom of pair of fragments can be selected and the following command issued to match the selected fragments only:

```
>>match
```

The match macro also takes the '-i' option. When this option is given, the procedure will try to match the first fragment and the second one with the inverted coordinates. The result will be printed as the RMSD and the transformation matrix, use the '-a' option to align the fragments.

Note that if your molecule is disordered or has high symmetry, the automatic matching might fail. Also if there are Q-peaks in the structure, they should be hidden (Ctrl+Q) or deleted using the following commands:

```
>>kill $Q
```

Since graph matching algorithm implementation does not use any pattern recognition for the optimisation, high symmetry may introduce huge number of possible graph permutations (like each CH₃ group increases the number of permutations by a factor of 6 (3!)), it is recommended to hide the H atoms (Ctrl+H). If this does not help, a manual change of atom types may be required to break the symmetry.

If automatic alignment fails due to the difference in the connectivity of the fragments, the user might select at least three atoms of one fragment and the same number of atoms in another fragment in matching sequence and type

```
>>match
```

to match fragments using only the selected atoms.

There is also a matching mode, which can be activated by typing:

```
>>mode match
```

This mode enables interactive matching by a maximum of three pairs of atoms. The first pair of atoms are superimposed, the second one causes the rotation to minimize the distance between the atoms of the second pair, the third pair causes rotation around the line formed by the first and second pair to minimize the difference between the atoms of the third pair.

Olex2 also provides a way to load an extra structure on screen. That structure can also be used in all the matching procedures described above. To load an extra structure, type:

```
>>reap -* [file_name]
```

if the file name is not given, the 'File Open' dialog will appear.

*The fragment connectivity can be adjusted using the AddBond, DelBond and the Conn commands. For example if the compound under the consideration is a metal complex with two or more identical ligands, the ligands can be 'detached' from the metal by selecting the metal atom and typing

```
>>conn o
```

4. 2 Copy naming scheme from one fragment to another

Section above describes how to match/overlay fragments. This section describes how to transfer labelling scheme from one fragment to another for consistent labelling. Note that if the '-i' option was used for the matching, it also should be used for the naming.

An atom of the fragment with the original naming scheme and an atom of the fragment to which the naming scheme to be transferred should be selected, then the following command have to be typed:

```
>>match -n=mask
```

If the mask starts from '\$' or '-' a special action is taken. The '\$' character instructs the procedure to replace the give number of characters after the '\$' in atom labels with the characters, for example:

```
match -n=$2
```

will replace labels like C101, Cu10, C10a to C201, C20a and Cu20.

The '-' instructs the procedure to replace the ending chars of the labels with the give characters, for example:

```
match -n=-b
```

will replace labels like C101, Cu10, C10a to C10b, C10b and Cu1b.

Any other values of 'mask' are simply added to the labels, like

```
match -n=a
```

will replace labels like C101, Cu10, C10a to C201a, C10a and Cu10a.

Note that the labels may become invalid for the use with some programs and will be trimmed/changed on the next file input/output operation.

Atom name suffix* can be changed by the following command:

```
>>name [atoms] -s=[suffix]
```

if no atom names provided, suffix of all atoms will be changed to the provided one or removed (if no value is provide for the '-s' option)

*The suffix here is assumed the ending of the atom name following the atom symbol or any number, e.g.:

for C12a, suffix is 'a'

for C12 the suffix is empty

for Cz the suffix is 'z'

4. 3 Get esd's on geometric measurements

Olex2 can calculate esd's on a variety of geometric measurements, also if a CIF is loaded into Olex2 then esd's available in the CIF (bond lengths and the angles) will be displayed in the tooltip when hovering over the bonds or selection of the bonds; use the 'sel' command to print the values in the console.

To calculate the esd's Olex2 need the variance-covariance matrix. This can be readily produced by shelxl when refining with a negative MORE instruction (like MORE -1). It also will be soon available from the smtbx refinement. Once the matrix file is available, the geometric parameters can be easily calculated by selecting:

a bond or two atoms - length

two bonds or three atoms - angle

four atoms - torsion angle and the tetrahedron volume

a plane - RMSD and the centroid coordinates in fractional and Cartesian coordinates

a plane and an atom - atom to plane and atom to plane centroid distances

a plane and a bond - angle between the plane normal and the bond

two planes - angle between the plane normals, plane centroid to plane centroid, plane to centroid and the shift between the plane centroids distances

three planes - the angle between the plane centroids

Then type:

```
>>esd
```

to get the measurements with esd's.

Note that the current implementation of the esd calculation procedure does not consider symmetry constraints and gives esd's even for the symmetry related parameters.

4. 4 Get a stereo view

There are four stereo modes available in Olex2:

- Color stereo (resulting in monochrome stereo image)
- Anaglyph stereo (resulting in grey-scale color for colors matching with colors of the glasses)
- Rendering of two spatially separated projections
- Hardware stereo

The first three modes do not put any constraints on the hardware besides that the graphics card should be able to render two image of the scene with convenient frames per second (fsp). These modes work with 'standard' red-green or cyan-blue glasses.

The hardware 3D stereo requires special graphics card and 3D stereo glasses. A test stand we have to demonstrate the hardware 3D stereo is built using the following components:

- 120Hz refresh rate display (we have Samsung)

- NVIDIA® 3D active shutter glasses (we have NVIDIA 3D vision kit)
- NVIDIA® Quadro FX graphics card (we have the low end FX580)

The standard NVIDIA® 3D vision kit is designed for the games and works only with the DirectX® based games (it is Windows® specific too). The Quadro series of the graphics cards provide a generic, OpenGL® based, portable mechanism for the 3D stereo rendering.

To switching stereo mode on/off use either the View tab of the GUI, or the following command:

```
>>gl.Stereo({none, cross, color ,anaglyph, hardware}, [angle=3]),
```

by providing the angle argument the viewing angle can be changes, the angle is signed and by inverting the sign the left and right projections are swapped.

To change the projection colours use the following command:

```
>>gl.StereoColor({lef,right}, R,G,B[,A])
```

R,G,B and A (optional) are the color components, floating point numbers in range of [0,1]. For example to set color of the left (mind the note above about the viewing angle) projection to red and of the right projection to cyan colors:

```
gl.StereoColor(left,1,0,0)
gl.StereoColor(right,0,1,1)
```

4. 5 Pack or grow molecule(s)

There are several commands in Olex2 to grow and pack molecules. First command is 'grow', this command grows all atoms in the asymmetric unit. Grow command will generate the molecule until all newly available growing matrices differ only by translation part, this will create complete set of atoms for discrete molecules and generate quite a large fragment for polymeric structures. If a particular symmetry operator needs to be used, the 'sgen' command might be useful, for example:

```
>>sgen 1556 $N
or
>>sgen x,y,z+1 $N
```

will generate all nitrogen atoms using the x,y,z+1 symmetry operator (the identity operator, x,y,z is always the first operator in Olex2). If no atoms provided, all atoms will be generated. It is also possible to click on an atom which can be grown, and choose the 'Grow' option from the menu.

To find out the set of operators for loaded structure, use:

```
>>ltsymm
```

There is also growing mode (look in the table for all related options of this mode), which provides visual and metric information about bonds which can be generated. The mode allows using one symmetry operator a time:

```
>>mode grow
```

The growing command generates only fragments which can grow; sometimes it is needed to generate the rest of the asymmetric unit as well, like after growing the main fragment all related solvent molecules need to be generated. For this use the 'grow -w' command, which will apply already existing symmetry matrices to whole asymmetric unit.

The information about matrices which can grow an atom (if on a special position) or a bond can also be found using the 'envi' command. To find out atoms in special position, use the 'degen' command, which prints the atomic position multiplicity (unless it is 1).

The pack command can be used to pack molecules or particular atoms. For example:

```
>>pack R
```

generates molecules which centre of mass is within sphere of R radius

```
>> pack cell
```

Shows the content of the unit cell. Use 'grow -w' to show all molecules contributing atoms to the unit cell.

```
>>pack $Fe
```

packs only specified atoms, '-c' option can be added to specify that current model should not be cleared.

```
>>mode move [-c]
```

once a fragment atom is selected this mode will copy (if '-c' is provided) or move any other fragment (which is clicked) as close to the selected atom as possible.

```
>>mode pack
```

Displays asymmetric units as a set of tetrahedron, clicking on which generates the asymmetric unit using that particular transformation.

The structure analysis commands like 'pipi' and 'htab' provided with '-g' option can also be used to grow molecules and visualise some particular interactions.

Finally, to show the asymmetric unit, type

```
>>fuse
```

4. 6 Change P1 space group to P-1

Identify two atoms related by the center of inversion, select them and type

```
>> echo ccrd()
```

to get coordinates of the point between the selected atoms. This will be fractional coordinates of the proposed centre of inversion as 'x,y,z'. The type:

```
>> push -x -y -z
```

to move the content of the asymmetric unit so that the centre of inversion now is at (0,0,0). Then type:
>>changesg P-1

to change the space group. Olex2 will try to remove the symmetry related atoms, however if the atoms do not overlap within some value, they have to be removed manually or by typing:

>>fuse *r*

command, where *r* is the radius within which atoms of the same type get merged into a single one.

Sometimes the molecule looks 'broken' after this operation and the command 'compaq -a' has to be executed to assemble the molecule .

4. 7 Change space group settings

Olex2 provides the 'sgs' command to change the space group settings (cell choice and the axis). For a monoclinic space group, type:

>>sgs axis_cellchoice [output HKL file name]

For example:

>>sgs b1 b1.hkl

changes the current space group setting to make the 'b' the principal axis and for the cell choice '1' and creates the b1.hkl file with transformed reflections. It is also possible to enter just the principle axis, like 'a' or 'c'. Please note that the cell esd's will be estimated since no variance-covariance matrix is available for the transformation.

For orthorhombic space groups, at the moment, only 'sgs abc' is valid to transform settings to standard. Olex2 will change the cell settings accordingly, modify all the atomic coordinates and the APS's (if any) and, if the output HKL file name is provided, creates the new HKL file according to the transformation. You will have to choose that file for the refinement if needed.

To find out current space group settings, type:

>>echo sgs()

4. 8 To control console and graphics visibility

Olex2 has a built in console for typing commands. Sometimes it is desirable to see only the text (output) or the structure. There are several commands and shortcuts to help with this. <Ctrl>+T toggles whether the molecule is displayed or not. So, if your molecule has inexplicably disappeared, it's always worth pressing this key combination...

The program output of Olex2 happens 'behind' the molecule. The wisdom of doing things this way can be debated, but it means that there are fewer windows cluttering your screen. It is possible to adjust the number of lines of output you see by typing:

>>lines *n*

(e.g. **lines 5**) to see only 5 lines of the output a time, it may be confusing for procedures producing more than 5 lines (like calcvold). If you want to see all lines, type:


```
>>lines -1
```

Alternatively, you can type 'text' in the console (or use corresponding GUI links) to view the text output in an external text editor. You can always use PgUp and PgDn keys to scroll the console output. There is a limited buffer to hold the console output, however a full transcript of the Olex2 session is available in the log file, which can be displayed using:

```
>>log
```

command.

4. 9 Select atoms that became 'too small'

By default, the size of the atom displayed on the screen is proportional to its ADP or Uiso. If the atom type is wrong, and the real element is much heavier, the Ueq will become very small and therefore the displayed sphere will be too small to select by mouse.

There are two solutions to this problem:

- 1) You can select an area that includes the atom you wish to select by drawing a box around the atom with the Shift key and the left mouse button pressed simultaneously.
- 2) You can switch the view to a Ball and Sticks display (View>Quick Drawing Styles) or type:

```
>>pers
```

Also use (or the GUI):

```
>> telp
```

to switch back to the view when the atoms' proportional Uiso and ADP's are displayed.

4. 10 Use ShelX programs in Olex2

ShelXL, ShelXLMP, ShelXS and ShelXM executables are available free for academic use from George Sheldrick. If ShelX programs are on the system path, then Olex2 will be know that ShelX is installed. You should not put the (use a folder which is on the PATH) the ShelX executables alongside the Olex2 executable (on Windows or Linux) or in the olex2.app/Content/MacOS folder (on Mac).

All ShelX commands are – or at lease should be – processed by Olex2 correctly. Please let us know immediately if any correct ShelX command does not behave the way you expect it to behave.

4. 11 Change default programs

To change default text editor, html editor or folder browser, you need to set the Olex2 variables associated with these programs. To keep the changes permanent, create the file 'custom.xld' in the Olex2 installation directory. For example the following construct placed in that file sets programs for KDE:

```
<user_onstartup help="Executes on program start"
<body <args>
  <cmd
    <cmd1 "setvar(defeditor,'kate')">
```

```

<cmd2 "setvar(defexplorer,'konqueror')">
<cmd3 "setvar(defbrowser,'konqueror')">
>
>

```

This defines a function which is called when Olex2 starts up, please note if there are several functions with the same name are found in the files - the last one will be used. Please avoid overriding any functions in the macro.xld file as that may cause Olex2 to function incorrectly.

4. 12 Working with the Maps display

The 2D map can be operated by the following controls:

- Expand/Shrink – Ctrl l+ right mouse button
- Level change – Shift + right mouse button (only in the Contour view)
- Z change – Ctrl + left mouse button
- xgrid.PlaneSize() - prints or sets the plane size. The default value of the plane - is the 128x128 pixels, if you have a high performing graphics card, you can set the value to 256, 512, 1024 or other power of two values.

4. 13 Fix tooltips problems

Functionality :

```
>>GlTooltips(bool)
```

```
>>echo GlTooltips()
```

These two commands allow modifying or querying current tooltip management. By default there are native tooltips for Windows and OpenGL emulated ones for the other platforms. The reason in the distinction is that native tooltips on Mac are rendered not at the time they were set (at least with wxMac), but after. This leads to displaying previous tooltip instead of current. The case of GTK is still under the investigation, but on older versions of tooltips would not be rendered. This can be overridden using the GlTooltip(true/false) command, the setting will be saved upon normal program termination. Rendering of the native tooltips on platforms, other than Windows will degrade the performance, since all mouse movement events (unless a mouse button is pressed) will cause the scene re-drawing. Using the OpenGL emulation of the tooltip will render the scene only when the mouse movement stopped for at least 1/2 of the second.

To control the OpenGL tooltip emulation appearance the user can use the following command:

```
>>editmaterial Tooltip
```

5. Appendix

5. 1 About Versions and Tags

The Olex2 distribution system has undergone many changes since the project was started in 2004. We have always aimed at providing program updates as soon as possible to the Olex2 user community. We think that one of the best ways to encourage bug reports and suggestions is to translate this user feedback as soon as possible into real improvements in the software.

For a while - up to about December 2009 - we have made updates available on a very frequent basis. This has met with a warm welcome from many of our users, but has also caused some problems: Not all updates did *only* do what they were supposed to do! At that point, we have decided to change the policy somewhat, and have come up with the following system for the distribution of Olex2.

There are now distinct versions of Olex2. Before Version 1.0, everything consisted of continuously updated files. At some point, this became no longer supportable, and we decided to introduce proper versions into the Olex2 distribution system. Any new version requires a complete re-install. However different versions of Olex2 can exist next to each other without causing any interference. For each version of Olex2, there are three 'tags', referring to different source repositories. For example, for Version 1.1 there are the following tags:

- 1.1-alpha
- 1.1-beta
- 1.1

Alpha: Whenever we made some changes, we 'make' an *alpha* distribution of Olex2. We use this version for in-house testing (although you are very welcome to use this version too, as long as you are aware of the fact that this version is typically very experimental and will very likely cause some problems. However, if you have suggested a new feature, or reported a bug fix, you may well find that we have implemented your suggestions already!

Beta: Once we've done some testing of this alpha version, we 'promote' it to the *beta* distribution. This version is tested by a wider group of testers - these tend to be those users with whom we have a lot of contact.

Release: Once a distribution has been tested in the *beta* stage, a proper release is made. This can be expected to be stable and if you encounter any problems with release version, please tell us about this! It doesn't matter how small the problem is, we'd like to know.

5. 2 Installing Olex2

5. 2. 1 Windows:

- Please download the Olex2 installer from the Windows tab and run it. Select the destination folder to which to install Olex2 (typically **C:\Program Files\Olex2**). If you

do not have administrator privileges*, please select a folder where you have full access rights.

- Make sure you select the latest version of Olex2—Version 1.1—from the download repository.
- Click on **Install**. This will install Olex2 on your computer. When it is done, there will be a 'Run' button on the installer form. Click this to run Olex2. The first time Olex2 runs on your computer, it will take some time to start up (up to one minute!).

Olex2 should now be opened, there should be no red (error) lines in the main window and there should be a molecule of sucrose displayed on the screen. Olex2 does not require any third party programs to perform structure analyses—Structure Solution as well as Structure Refinement—but, if you have a ShelX licence, you may want to make sure that Olex2 can interact with the ShelXS, ShelXL and ShelXM. If you do not have a ShelX licence, and would like to obtain one, please go to the [ShelX Pages](#) for more information.

Please note that the ShelX executables that are shipped with WinGX do not work with Olex2.

You can either copy your ShelX executables into the Olex2 installation folder, or—better—you can copy your executables into a folder which you then add to the PATH variable of Windows. For example, create a folder **C:\Program Files\Shelx**, then Right-Click on 'My Computer' (XP) or 'Computer' (Vista and 7) and select *Properties*. Then select *Advanced*. There you can add the location of your ShelX executables to the PATH variable.

5. 14 External Programs

5. 14. 2 SHELX

All programs of the SHELX family can interact seamlessly with Olex2. There is no need for registering any of these programs with Olex2, it is enough if the folder containing the ShelX programs are on the system PATH. This is normally the case if ShelXTL has been installed on a system. Otherwise, you will need to set you system PATH variable to include the folder where you keep your SHELX executables.

Please note that the SHELX executables that are shipped with WinGX do not work with Olex2. These executables have been modified in such a way that they will only work properly with WinGX. Since WinGX puts the folder that contains these executables on the system PATH, you might find that SHELX appears in Olex2 - and then doesn't work. In this case, you will need to get new SHELX executables and put them in the same folder where Olex2 is installed - executables found there will be used by Olex2 preferentially.

5. 14. 3 Platon

John Warren has provided an interface to PLATON.

5. 14. 4 SuperFlip

Arie van der Lee has provided an interface to SuperFlip.

5. 15 About Macros and Scripting in Olex2

Olex2 supports two different types of external scripting: Macros and Python scripts.

References

¹ Acta A45 (1989), 208